

## Bolt Hole Anchor

### Part #: 00230

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Custom configurations not available. Not repairable. Contact customer service for details.

Bolt Hole Anchor is suitable for the following applications:



**Personal Fall Arrest:** Bolt Hole Anchor may be used to support a MAXIMUM 1 Personal Fall Arrest System (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use. Applicable D-ring: Dorsal.



**Restraint:** Bolt Hole Anchor may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.



**Work Positioning:** Bolt Hole Anchor may be used in Work Positioning applications. Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. Maximum allowable free fall is 2'. Applicable D-rings: Side, Shoulder.

**For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-310 lbs., or up to 420 lbs. if used in combination with equipment explicitly certified for such use.**



**WARNING** Use of equipment in unintended applications may result in serious injury or death. Maximum 1 attachment per connection point.

Materials: galvanized steel, stainless steel, and aluminum.

Bolt Hole Anchor may be installed in steel substrates ONLY.

MINIMUM substrate thickness: 1/4".

MINIMUM installation distance from all edges or corners: 2".

Compatible hole diameter: 3/4" - 1 1/4".

MAXIMUM 1 user per Bolt Hole Anchor.

Bolt Hole Anchor may be used in either overhead or horizontal applications, and may be used in combination with horizontal lifelines.

UPC-A Code: 672421002309

