

# Standing Seam Roof Clamp

**Part #: 00250**

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Custom configurations not available. Not repairable.  
Contact customer service for details.



Standing Seam Roof Clamp is suitable for the following applications:



**Personal Fall Arrest:** Standing Seam Roof Clamps may be used to support a MAXIMUM 1 Personal Fall Arrest System (PFAS), which includes a self-retracting lifeline, for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 2'. Applicable D-ring: Dorsal.



**Restraint:** Standing Seam Roof Clamps may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.



**Rescue/Confined Space:** Standing Seam Roof Clamps may be used in Rescue/Confined Space applications. Rescue systems function to safely recover a worker from a confined location or after exposed to a fall. There are various configurations of Rescue systems depending on the type of rescue. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. No free fall is permitted. Applicable D-rings: Dorsal, Chest, Shoulder.

**For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-310 lbs., or up to 420 lbs. if used in combination with equipment explicitly certified for such use.**

Materials: powder-coated steel.

MAXIMUM 1 connection per Standing Seam Roof Clamp.

Refer to product instructions for list of incompatible roof seams. NEVER install on incompatible roof.

Adjusts to fit roof seams between 24" - 36" in width.

Compatible with SRLs up to 65' in length.

SRLs from 50' - 65' require Retractable Swivel Adapter (product #: 10975).

UPC-A Code: 672421002507