

SkyMast

GUARDIAN

FALL PROTECTION

Part #	Weight	Description
00271	40.8 lbs.	SkyMast Anchor w/3 SRL Cradles
00315	14 lbs.	SkyMast Skyhook. Applicable roof pitch: 1/12 - 3/12.
00325	14 lbs.	SkyMast Skyhook. Applicable roof pitch: 4/12 - 6/12.
00335	14 lbs.	SkyMast Skyhook. Applicable roof pitch: 7/12 - 9/12.
00345	14 lbs.	SkyMast Skyhook. Applicable roof pitch: 10/12 - 12/12.

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Custom configurations not available. Not repairable. Contact customer service for details.

SkyMast is suitable for the following applications:



Personal Fall Arrest: SkyMast may be used to support a MAXIMUM 1 Personal Fall Arrest System (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use. Applicable D-ring: Dorsal.



Restraint: SkyMast may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-310 lbs., or up to 420 lbs. if used in combination with equipment explicitly certified for such use.



WARNING Use of equipment in unintended applications may result in serious injury or death. Maximum 1 attachment per connection point.

Materials: zinc-plated steel.

SRLs and SkyMast Skyhook sold separately.

MAXIMUM 3 users per SkyMast.

UPC-A Codes:

00271: 672421002712; 00315: 672421003153;
00325: 672421003252; 00335: 672421003351;
00345: 672421003450

