

D-Ring 2 Hole Anchor

Part #: 00360

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

GUARDIAN
FALL PROTECTION



D-Ring 2 Hole Anchor is suitable for the following applications:



Personal Fall Arrest: D-Ring 2 Hole Anchors may be used to support a MAXIMUM 1 Personal Fall Arrest System (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use. Applicable D-ring: Dorsal.



Restraint: D-Ring 2 Hole Anchors may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.



Work Positioning: D-Ring 2 Hole Anchors may be used in Work Positioning applications. Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. Maximum allowable free fall is 2'. Applicable D-rings: Side, Shoulder.



Rescue/Confined Space: D-Ring 2 Hole Anchors may be used in Rescue/Confined Space applications. Rescue systems function to safely recover a worker from a confined location or after exposed to a fall. There are various configurations of Rescue systems depending on the type of rescue. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. No free fall is permitted. Applicable D-rings: Dorsal, Chest, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-420 lbs.

Minimum substrate thickness requirements: Wood: 4" x 4" x 4" block. Metal: 1/4". Concrete: 4--1/2".

Fastener recommendations: Wood: (2) 1/2" diameter, 3" long lag bolts. Metal: (2) 1/2" diameter, grade 8 bolts and hardware (length determined by Competent Person). Concrete: (2) 1/2" diameter, 3" long Power-Bolts.

Materials:

Plate: Stainless Steel.

D-ring: Zinc-Plated Steel.

MAXIMUM 1 connection per D-Ring 2 Hole Anchor.

UPC-A Code: 672421003603