

Halo Anchor

Part #: 00482

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Custom configurations not available. Not repairable. Contact customer service for details.

Halo Anchor is suitable for the following applications:



Personal Fall Arrest: Halo Anchors may be used to support a MAXIMUM 1 Personal Fall Arrest System (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use. Applicable D-ring: Dorsal.



Restraint: Halo Anchors may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.



Work Positioning: Halo Anchors may be used in Work Positioning applications. Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. Maximum allowable free fall is 2'. Applicable D-rings: Side, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-420 lbs.

Materials: forged steel, zinc-plated steel, and rubber.

MAXIMUM 1 connection per Halo Anchor.

Minimum substrate thickness requirements:

Wood: 3/4" CDX or better. Metal: 20 gauge or better.

Fasteners included. Installation requires (6) 1/4" x 3" lag screws OR (12) 16d nails.

All fasteners must be fully embedded into substrate.

Suitable for use in horizontal lifeline (HLL) applications. All set-up, installation, and use of HLLs must be done under the supervision of a Qualified Person.

UPC-A Code: 672421004822

GUARDIAN
FALL PROTECTION

