

Cable HLL System

Part #: 04800

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Custom configurations available. Contact customer service for details.

Cable HLL System is suitable for the following applications:



Personal Fall Arrest: Cable HLL System may be used to support a MAXIMUM 2 Personal Fall Arrest Systems (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6'. Applicable D-ring: Dorsal.



Restraint: HLL System may be used in Restraint applications to support a maximum 2 PFAS. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-310 lbs. per worker.

NEVER for simultaneous use in Fall Arrest and Restraint applications.

Materials: polyester, galvanized steel, and zinc-plated steel.

Cable diameter: 3/8".

Maximum span length: 100'.

Required Cable HLL System line sag: 6", measured from center of span.

Maximum 2 connections per Cable HLL System.

UPC-A Code: 672421048000

