

2-Way Standing Seam Roof Clamp

Part #: 10600

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Custom configurations not available. Not repairable. Contact customer service for details.



2-Way Standing Seam Roof Clamp is suitable for the following applications:



Personal Fall Arrest: 2-Way Standing Seam Roof Clamps may be used to support a **MAXIMUM 1** Personal Fall Arrest System (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use. Applicable D-ring: Dorsal.



Restraint: 2-Way Standing Seam Roof Clamps may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-310 lbs., or up to 420 lbs. if used in combination with equipment explicitly certified for such use.

Materials: zinc-plated steel.

MAXIMUM 1 connection per 2-Way Standing Seam Roof Clamp.

MINIMUM required seam thickness: 24 gauge.

For installation onto compatible roof seams ONLY. A Qualified Person must determine seam compatibility. Please contact Guardian Fall Protection with any questions regarding roof seam compatibility.

Not for use in a horizontal lifeline system.

UPC-A Code: 672421106007