

Concrete Anchor Strap

Part #	Length	Description
10705	3'	Concrete Anchor Strap w/Loop & D-ring Ends
10710	3'	Concrete Anchor Strap w/Loop & D-ring Ends & Protective Sheathing
10715	4'	Concrete Anchor Strap w/Loop & D-ring Ends & Protective Sheathing
10717	6'	Concrete Anchor Strap w/Loop & D-ring Ends & Protective Sheathing
10720	4'	Concrete Anchor Strap w/Loop Ends

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Custom configurations available. Not repairable. Contact customer service for details.

Concrete Anchor Strap is suitable for the following applications:



Personal Fall Arrest: Concrete Anchor Straps may be used to support a MAXIMUM 1 Personal Fall Arrest System (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use. Applicable D-ring: Dorsal.



Restraint: Concrete Anchor Straps may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.



Work Positioning: Concrete Anchor Straps may be used in Work Positioning applications. Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. Maximum allowable free fall is 2'. Applicable D-rings: Side, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-310 lbs., or up to 420 lbs. if used in combination with equipment explicitly certified for such use.

Materials: stainless steel and heavy duty nylon.

Must be installed onto rebar prior to pouring concrete. Concrete must be fully cured prior to use.

MAXIMUM 1 connection per Concrete Anchor Strap.

UPC-A Codes:

10710: 672421107103

10715: 672421107158

10717: 672421107172

