

Yellow Jacket SRL

GUARDIAN
FALL PROTECTION
PERFORMANCE SAFETY GEAR

Part #	Length	Description
10946	10'	Heavy Duty Cable SRL w/Shock Pack
10950	10'	Cable SRL w/High Strength Swivel Snap Hook
10952	10'	Cable SRL w/Aluminum Rebar Hook
10956	10'	Cable SRL w/High Strength Non-Indicating Snap Hook
10957	10'	Cable SRL w/High Strength Indicating Snap Hook

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.14-12, and ANSI A10.32-2012 regulations.

Custom configurations available. Contact customer service for details.

Yellow Jacket SRL is suitable for the following applications:



Personal Fall Arrest: Yellow Jacket SRLs may be used in Personal Fall Arrest applications as a component of a MAXIMUM 1 Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Applicable D-ring: Dorsal.

- Standard applications: No free fall is permitted. SRL must always be positioned at or above harness dorsal D-ring AND at or below anchor point.
- Leading Edge (LE) applications: Maximum 2' free fall. SRL may be positioned a maximum 2' below harness dorsal D-ring or a maximum 2' above anchor point.



Restraint: Yellow Jacket SRLs may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-310 lbs., or up to 420 lbs. if deemed permissible by a Competent Person and used in combination with equipment explicitly certified for such use.

Part # 10946 may be used in LE applications. All other part #s may be used in LE applications if used in combination with a shock absorber extension deemed compatible with SRL by a Competent Person.

Materials: aluminum, galvanized steel, stainless steel, and zinc-plated steel.

May be used in either mobile or stationary applications. For mobile applications, attach SRL carabiner to harness Dorsal D-ring, and attach snap hook to selected anchorage connector. For stationary applications, attach SRL carabiner to selected anchorage connector, and attach snap hook to applicable harness D-ring.

MAXIMUM 1 user per Yellow Jacket SRL.

UPC-A Codes:

10946: 6 7242110946 6
10950: 6 7242110950 3
10952: 6 7242110952 7
10956: 6 7242110956 5
10957: 6 7242110957 2

Packing Dimensions:

#10946 & #10950
16"L x 4"W x 5"H.
Weight: 7 lbs.
Quantity: 200 per pallet;
1,450 lbs. total.

Packing Dimensions:

#10952
9¼"L x 10"W x 5¼"H.
Weight: 10 lbs.
Quantity: 75 per pallet;
800 lbs. total.

Packing Dimensions:

#10956
8¼"L x 8"W x 3"H.
Weight: 4½ lbs.
Quantity: 100 per pallet;
5,000 lbs. total.



Repairable by the manufacturer. Contact customer service for details.