

## Skyhook Swivel Top

### Part #: 00380

When used in combination with Guardian Fall Protection Skyhook Anchor, compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Custom configurations not available. Not repairable. Contact customer service for details.

Skyhook Swivel Top is suitable for the following applications:



**Personal Fall Arrest:** Skyhook Swivel Top may be used to support a MAXIMUM 1 Personal Fall Arrest System (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use. Applicable D-ring: Dorsal.



**Restraint:** Skyhook Swivel Top may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.



**Work Positioning:** Skyhook Swivel Top may be used in Work Positioning applications. Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. Maximum allowable free fall is 2'. Applicable D-rings: Side, Shoulder.

**For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-420 lbs.**



**WARNING** Use of equipment in unintended applications may result in serious injury or death. Maximum 1 attachment per connection point.

**Skyhook Swivel Top must ALWAYS be used in combination with Guardian Fall Protection Skyhook Anchor.**

Materials: powder-coated steel.

Install to Skyhook Anchor using clevis pin and hitch pin. Always ensure Skyhook Swivel Top is fully secured to Skyhook Anchor prior to use.

Compatible with SRLs up to 65' in length. SRLs from 50' - 65' require Retractable Swivel Adapter (part # 10975). Install SRL into Skyhook Swivel Top by passing clevis pin through Skyhook Swivel Top and SRL connection point, and securing with hitch pin.

UPC-A Code: 672421003801

