

Bridge Guard™

GUARDIAN
FALL PROTECTION

Part #	Height	Description
04725	43 lbs.	75" Post w/2-Way Topper
04726	55 lbs.	75" Post w/4-Way Topper
04727	15 lbs.	Intermediate Bridge Guard™ Post (for runs between 60' - 90')
04728	28 lbs.	2-Way Topper (for Bridge Guard™ only)
04729	40 lbs.	4-Way Topper (for Bridge Guard™ only)

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Custom configurations not available. Not repairable. Contact customer service for details.

Bridge Guard is suitable for the following applications:



Personal Fall Arrest: Bridge Guards may be used in Fall Arrest applications to support a compatible HLL system for a MAXIMUM 2 Personal Fall Arrest Systems (PFAS) per HLL span. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use. Applicable D-ring: Dorsal.



Restraint: Bridge Guards may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-310 lbs., or up to 420 lbs. if used in combination with equipment explicitly certified for such use.



WARNING Use of equipment in unintended applications may result in serious injury or death. Maximum 1 attachment per connection point.

Materials: aluminum.

Lifeline must be 3/8" aircraft cable (part # 04800). No additional shock absorbing component is required. Bridge Guard Topper is designed to bend and deform to absorb forces of fall arrest.

MAXIMUM 2 users per Bridge Guard™ HLL.

UPC-A Codes:

04725: 672421047256

04726: 672421047263

04727: 672421047270

04728: 672421047287

04729: 672421047294

