

CD-10

PRODUCT DATA SPECIFICATIONS

PRODUCT DESCRIPTION

The OMG CD-10 is a hammer-in, non-threaded fastener designed to secure insulation and single-ply membrane to structural concrete. This fastener is available in 2-in. to 12-in. lengths. The CD-10 is Factory Mutual and Miami-Dade County approved.

FEATURES & BENEFITS

- Diamond point allows easier installation and less chance of hole damage.
- Split bulb exerts pressure on walls of hole, producing remarkable holding power.
- Strongest hammer-in fastener available.
- Typical pullout values in cured concrete (3000 psi) are over 800 lbs. A pullout test is recommended.
- The OMG CD-10 is F.M. and Miami-Dade County approved.

COATING

OMG CR-10 corrosion resistant coating exhibits less than 15% red rust after 30 Kesternich cycles. CR-10 coating exceeds F.M. Approval Standard 4470.

APPLICATION

Predrill a 7/32-in. hole using a carbide drill bit. The fastener is then installed with a 2 lb. short-handle sledge hammer.

Minimum fastener embedment into the deck should be 1-in. The predrilled hole must be a minimum of 1/2-in. deeper than fastener embedment.

Note: Prior to job start, contact OMG to perform a pullout test to determine the pullout values. Also, care must be taken not to overdrive the fastener causing subsequent damage to the insulation facer.

PLATES & ACCESSORIES

Appropriate steel or plastic plates, depending on application. **See Plates section.** Use a 7/32-in. carbide tip SDS or straight shank drill bit.

APPROVALS



USE WITH
SC
DECK
TYPES

PHYSICAL DATA

The data below is constant for each OMG CD-10.

HEAD	SPLIT BULB
Flat Top Pan .435" Diameter .115" Height	.270/.277" Diameter
	COATING
	CR-10

ORDERING INFORMATION

CAT. NO.	LENGTH	PKG	WEIGHT
CD002	2"	500	13 lbs.
CD212	2½"	500	16 lbs.
CD003	3"	500	18 lbs.
CD312	3½"	500	21 lbs.
CD004	4"	500	23 lbs.
CD412	4½"	500	25 lbs.
CD005	5"	500	28 lbs.
CD512	5½"	500	31 lbs.
CD006	6"	500	33 lbs.
CD007	7"	500	38 lbs.
CD008	8"	500	44 lbs.
CD009	9"	250	25 lbs.
CD010	10"	250	28 lbs.
CD011	11"	250	31 lbs.
CD012	12"	250	33 lbs.

RP0912AE



FASTENERS ADHESIVES DRAINS PIPE SUPPORTS

KEY:

- S** Steel
- W** Wood
- G** Gypsum
- P** Purlins
- SC** Structural Concrete
- LC** Lightweight Concrete
- LWIC** Lightweight Insulating Concrete
- CWF** Cementitious Wood Fiber



CD-10

PRODUCT DATA SPECIFICATIONS

SPECIFICATION

The fastener will be an OMG CD-10 with a split diameter of .270/.277 and a 45° point angle. The fastener material must be a hard carbon steel per specification RM-03. The OMG CD-10 fastener will be used with a Factory Mutual approved, OMG round pressure plate. The fastener must be Factory Mutual approved and made in America.

COATING REQUIREMENT

The fastener will be coated with the OMG CR-10 corrosion resistant coating. When subjected to 30 Kesternich cycles (DIN 50018), the fastener must show less than 15% red rust and surpass Factory Mutual Approval Standard 4470.

APPLICATION

Predrill a 7/32-in. hole using a carbide tip SDS or straight shank bit. The CD-10 is then installed with a 2 lb. short-handle sledge hammer.

Minimum fastener embedment into the deck should be 1-in. The predrilled hole must be a minimum of 1/2-in. deeper than fastener embedment.

Note: Prior to job bid, contact OMG to perform a pullout test to determine the pullout values. Also, care must be taken not to overdrive the fastener causing subsequent damage to the insulation facer.

PHYSICAL DATA

The data below is constant for each OMG CR-10.

HEAD	SPLIT BULB
Flat Top Pan .435" Diameter .115" Height	.270/.277" Diameter
	COATING
	CR-10
POINT ANGLE	PACKAGING
45°	500, 250/carton

CR-10 LENGTH SELECTION PROCEDURE

1. If applicable, determine the thickness of the existing roofing material.
2. Add thickness of new insulation.
3. Add 1-inch minimum fastener penetration.
4. If odd size requirement, always size up in length, not down. See example:

	Example:	Your Project:
Existing Roofing	1 3/4"	
New Insulation	1/2"	
Min. Embedment	1"	1"
Total Fastening	3 1/4"	
Correct Length	3 1/2"	

The proper CD-10 for this example is 3 1/2 inches.



ROOFING PRODUCTS

153 BOWLES ROAD, AGAWAM, MA 01001
800-633-3800 WWW.OLYFAST.COM INFO@OLYFAST.COM

Copyright © 2009 OMG, Inc. All rights reserved.