

Stingray Anchor

GUARDIAN
FALL PROTECTION
PERFORMANCE SAFETY GEAR

Part #: 04730; 04731; 15048; 15049; 04736; 04737

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Custom configurations not available. Not repairable. Contact customer service for details.

Stingray Anchor is suitable for the following applications:



Personal Fall Arrest: Stingray Anchor may be used in Personal Fall Arrest applications to support a MAXIMUM 1 Personal Fall Arrest System (PFAS) if used as an independent anchorage connector. If Stingray Anchors are used as components of a complete and compatible horizontal lifeline (HLL), HLL system may be used to support a MAXIMUM 2 PFAS, unless conditions specified in instructions for a greater number of PFAS (up to 6 in entire system) are met. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. per PFAS in system. Maximum free fall is 6' unless used in combination with equipment explicitly certified for extended free fall up to 12'. Applicable D-ring: Dorsal.



Restraint: Stingray Anchor may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.



For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-420 lbs.

Materials: powder-coated steel.

When used in HLL applications, 300' MAXIMUM system length. MAXIMUM 60' between consecutive Stingray Anchors. For complete Stingray Anchor Systems longer than 60', intermediary Stingray Anchor(s) MUST be used.

Compatible Beam Flange Measurements:

Width: 5" - 13"

Maximum thickness: 3--3/8"

Part #	Description
15048	Stingray Absorbator System. Includes (1) Absorbator, (3) Shackles, (2) Thimbles, (1) Turnbuckle, (6) Fist Grips, & (2) 2½" O-rings.
15049	Stingray Absorbator System. Includes (2) Absorbinators, (4) Shackles, (2) Thimbles, (1) Turnbuckle, (6) Fist Grips, & (2) 2½" O-rings.
04730	Stingray Post Assembly for steel beam. Includes (1) Post, (2) L Brackets, (2) Threaded Rods, (2) Wing Nuts, & (1) Shackle. Standard base with 18" rod and standard flange hook. Does not include Pass-Through Top.
04731	Stingray Pass-Through Top. Includes hardware.
04736	Stingray 2 Post Kit. Includes (2) 04730 Post Assemblies, (1) 15049 HLL Attachment Absorbator System.
04737	Stingray 3 Post Kit. Includes (3) 04730 Post Assemblies, (1) 04731 Pass-Through Top, (1) 15049 HLL Attachment Absorbator System.

UPC-A Codes: 15048: 672421150482; 15049: 672421150499; 04730: 672421047300; 04731: 672421047317; 04736: 672421047362; 04737: 672421047379